




JAKANSONIC ULTRAGARSINĖS VALYMO VONIOS

Vaizdas	Modelis	Vonios talpa	Galingumas (W)		Vonios vidaus matmenys (mm)
			Ultragarso	Šildytuvo	
Mechaninė serija					
	PS-08	1.3L	60	/	150×140×65
	PS-10	2L	80	/	150x140x100
	PS-20	3L	120	100	240x135x100
	PS-25	4L	120	200	300x150x100
	PS-30	6L	180	200	300x150x150
	PS-40	10L	240	250	300x240x150
	PS-50	14L	300	400	300×240×200
	PS-60	15L	360	400	330×300×150
	PS-70	19L	420	600	330×300×200
	PS-80	22L	480	600	500×300×150
	PS-100	30L	600	800	500×300×200
Skaitmeninė serija					
	PS-08A	1.3L	60	50	150×140×65
	PS-10A	2L	80	50	150x140x100
	PS-20A	3L	120	100	240x135x100
	PS-25A	4L	120	200	300x150x100
	PS-30A	6L	180	200	300x150x150
	PS-40A	10L	240	250	300x240x150
	PS-50A	14L	300	400	300×240×200
	PS-60A	15L	360	400	330×300×150
	PS-70A	19L	420	600	330×300×200
	PS-80A	22L	480	600	500×300×150
	PS-100A	30L	600	800	500×300×200

Skaitmeninė serija su reguliuojamu galingumu (40 – 60 % reguliuojamas galingumas)					
	PS-20AL	3L	50~120	100	240x135x100
	PS-25AL	4L	120	200	300x150x100
	PS-30AL	6L	70~180	200	300x150x150
	PS-40AL	10L	100~240	250	300x240x150
	PS-50AL	14L	120~300	400	300x240x200
	PS-60AL	15L	150~360	400	330x300x150
	PS-70AL	19L	170~420	600	330x300x200
	PS-80AL	22L	200~480	600	500x300x150
	PS-100AL	30L	240~600	800	500x300x200

Vaizdas	Modelis	Vonios talpa	Galingumas (W)		Vonios vidaus matmenys (mm)
			Ultragarso	Šildytuvo	
Mechaninė serija be šildytuvo					
	PS-08T	1.3L	60	50	150x140x65
	PS-10T	2L	80	50	150x140x100
	PS-20T	3L	120	100	240x135x100
	PS-25T	4L	120	200	300x150x100
	PS-30T	6L	180	200	300x150x150
	PS-40T	10L	240	250	300x240x150
	PS-50T	14L	300	400	300x240x200
	PS-60T	15L	360	400	330x300x150
	PS-70T	19L	420	600	330x300x200
	PS-80T	22L	480	600	500x300x150
PS-100T	30L	600	800	500x300x200	
Pramoninė skaitmeninė serija (2 mm nerūdijančio plieno vonia, 40 – 60 % reguliuojamas galingumas)					
	KS-040	10L	240	500	300x240x150
	KS-060	14L	360	500	300x240x200
	KS-080	20L	480	500	330x300x200
	KS-100	30L	600	500	500x300x200
	KS-120	38L	720	1000	500x300x250
	KS-180	58L	1080	1000	550x350x300
	KS-240	78L	1440	2000	550x400x350
	KS-360	130L	2160	3000	650x450x450

Pastabos:

Dažnis: 28 - 42khz, 75 – 120khz - galima pasirinkti užsisakant

Vonios medžiaga nerūdijantis plienas SUS304 0.8mm

Laikmatis :1- 30 minutės

Šildymo temperatūra 20-80 laipsnių

Virš 6L talpos vonios su vandens išleidimo čiaupu

CE sertifikatas