

GUARD METALŲ APTIKIMO VARTAI

Eil. Nr.	Aprašymas
1.	<p>MODEL: XYT2101A6 (6 zones)</p> <p>Technical parameter Electric current: AC110V-240V,50/60HZ Power: <20W Net weight: 65KG Workplace environment: -20°C~+45°C Alarm: Sound alarm & LED light alarm Inner size:2000*700*510mm Outer size:2200*820*560mm Standard: GB15210-2003, CE</p>  <p>Characteristic & Function Sensitivity adjustable: Each zone has 100 degree sensitivity (Each zone sensitivity level from 0-99, whole sensitive level adjustment: 0-4095) Six mutual over-lapping detecting zones; Simultaneous alarm from multi-zones; (12 zones can be customized) 4 columns LED light alarm on both door panels, ascertain the layout of metal articles accurately 16 LED indicator lights for metal signal on the panel Easy operating, each function setting with corresponding keys Automatically count passengers and alarm times Harmless to human body: harmless with heart pacemaker, pregnant women, magnetic floppy, recording tapes, etc. Function: Walkthrough Metal Detector can easily detect weapons, such as knife and gun, and any metal articles which are hidden in human body.</p>
2.	<p>MODEL:XYT2101B(8-16-24 zones)</p> <p>PARAMETERS Power Supply:AC85V-264V . DC 12V 3.5A Working temperature:-20℃--+50℃ Working Frequency :4KHZ—8KHZ Waterproof can be used outside Standard External size: 2219mm(H)X898mm(W)X706mm(D) Standard Internal size: 2046mm(H)X750mm(W)X537mm(D)</p> <p>FEATURES</p> <ul style="list-style-type: none"> > Automatically System Testing > self-diagnostics when power on for the door panels, LED alarm sound, Zoning Management:4 size with LEDlight > The detection zone can be adjusted into 8, 16, 24 Zones. > Alarm Count: Passenger Count: > It can record 20000 alarm counts and can query the alarm time. > Detecting Speed: The maximum speed is 100 P/min, can downward adjust the detecting speed. > LCD backlight: 0-99S to display continuously, adjustable Recognition the size of the metal objects by different sound volume > Vibration Protection: Preventing vibration interference lead to false alarms > Alarm Sound: 1-25S alarm time, 0-255 adjustable alarm volume. LED Alarm: Four side with LED, light time 0-25S adjustable. > Sensitivity: Total value and zone value 0-255 degree adjustable > Can record and auto-save 9999 times, and can save passenger record to 65535 times at most. > Harmless to human body Control unit case and door panels can be freely combined to assemble, very easy to install & disassemble. > Working Application option for different sensitivity and detecting speed need, please select in the system. > Battery Backup not less than 2-8 hours. > Network support (Option) <p>System Management</p> <ul style="list-style-type: none"> > Fixed ID for the record. > English display. > Calendar: Display year, month, day, hour and minute. > Manage Encryption: To prevent the misuse causes the system unusual. > Restore Factory Settings, recover initial data. 
3.	<p>MODEL:XYT2101LCD (8-16-24 zones)</p> <p>Technical parameter Electric current: AC85V~264V/50-60HZ Power: <20W, low consume, low radiation Gross weight: 70KG Workplace environment: -20℃--+50℃ Standard: GB15210-2003, CE Standard External size: 2230mm(H)X835mm(W)X580mm(D) Standard Internal size: 1990mm(H)X700mm(W)X500mm(D)</p> <p>Characteristic & Function</p> <ul style="list-style-type: none"> > 5.7 inch LCD screen with Infrared remoter controller > Adopt advanced digital signal processing control replaced traditional analog signal control, better stability. > Friendly windows interface, both Chinese and English program, easy to operate. > Program Self-diagnostic when power on, automatically checking left and right door panel, LED light and choose the best working frequency. > Automatically count passengers and alarm times, keep alarm records for inquiry (up to 20000 records) > Detecting Zones: 6 detecting loops, can extend to 12,18zones by separate left, right, middle side detection to pinpoint detection (As follow picture) > Sensitivity adjustable: Each zone has 255 degree sensitivity level, three patterns: High, middle, Low for different requirements. Preset the metal size, weight, volume, location to exclude the coin, key, belt.. > Sound Alarm: 1-25s alarm time, 255 different sound volume and 12 tones for choose > LED light alarm: LED bar graph on left and right door frame, visible alarm simultaneously to ascertain the layout of metal articles > Lock and Password protection, only the authorized person can operate. > Anti-interference function, using advanced interactive transmitting and receiving to avoid interference, frequency range from 4K-8K to avoid frequency interference > 6 preset programs for security application versatility > 4 hours Battery backup, the uninterruptible power protection system secure the parameters when power off. > PVC material and Control unit on the top, waterproof, moisture-proof and cooler. > Integrated and modularized circuit design lead to simple installation and more convenient after services. > Adjustable Passing speed: up to 100 persons/min > Background light: 0-99 seconds for choose > Calendar function: real time display year, month, date, hour, minute, second > Harmless to heart pacemaker, pregnant women, magnetic floppy, recording tapes, etc. > Network support: (For Option) 
4.	<p>MODEL:XYT2101S (6-12-18 ZONES)</p> <p>Technical parameter Electric current: AC85V~264V/50-60HZ Power: <20W, low consume, low radiation Net weight: 70KG Workplace environment: -20℃--+45℃ Standard: GB15210-2003, CE Standard External size: 2230mm(H)X835mm(W)X580mm(D) Standard Internal size: 1990mm(H)X700mm(W)X500mm(D)</p> <p>Characteristic & Function</p> <ul style="list-style-type: none"> > LCD screen with Infrared remoter controller, both Chinese & English program, easy to operate. > Adopt advanced digital signal processing control replaced traditional analog signal control, better stability. > Program Self-diagnostic when power on, automatically checking left and right door panel, LED light and choose the best working frequency. > Detecting Zones: 18 detecting zones. Separate left and right side detection. Simultaneous alarm from multi-zones; > Sensitivity adjustable: Each zone has 255 degree sensitivity level, three patterns: High, middle, Low for different requirements. Preset the metal size, weight, volume, location to exclude the coin, key, belt. > Sound Alarm: 1-25s alarm time, 255 different sound volume for choose > LED light alarm: LED bar graph on left and right door frame, visible alarm simultaneously to ascertain the layout of metal articles > Password protection, only the authorized person can operate. > Anti-interference function, using advanced interactive transmitting and receiving to avoid interference, frequency range from 4K-8K to avoid frequency interference > 6 preset programs for security application versatility > Automatically count passengers and alarm times > Microprocessor control on top unit, anti-interference and self-diagnose transmission channel to avoid internal and external interference. > Easy assembly: designed with only 2 pieces cables and 8 screws, Simply-to-follow instruction. > Harmless to human body: is harmless with heart pacemaker, pregnant women, magnetic floppy, recording tapes, etc. > For option : Battery backup, 2-8 hours for option > For option : Network support 
5.	<p>MODEL:XYT2101A2 (6 ZONES)</p> <p>Technical parameter Electric current: AC85V~264V/50-60HZ Power: <20W, low consume, low radiation Net weight: 65KG Workplace environment: -20℃--+45℃ Standard: GB15210-2003, CE Standard External size: 2230mm(H)X835mm(W)X580mm(D) Standard Internal size: 1990mm(H)X700mm(W)X500mm(D)</p> <p>Characteristic & Function</p> <ul style="list-style-type: none"> > Program Self-diagnostic when power on, automatically checking left and right door panel, LED light and choose the best working frequency. > Adopt advanced digital signal processing control replaced traditional analog signal control, better stability. > Six mutual over-lapping detecting zones, Simultaneous alarm from multi-zones; > Sensitivity adjustable: Each zone has 255 degree sensitivity level, three patterns: High, middle, Low for different requirements. Preset the metal size, weight, volume, location to exclude the coin, key, belt. > Sound Alarm: 1-25s alarm time, 255 different sound volume for choose > LED light alarm: LED bar graph on left and right door frame, visible alarm simultaneously to ascertain the layout of metal articles > Automatically count passengers and alarm times > Password protection, only the authorized person can operate. > Anti-interference function, using advanced interactive transmitting and receiving to avoid interference, frequency range from 4K-8K to avoid frequency interference > Easy assembly: designed with only 2 pieces cables and 8 screws, Simply-to-follow instruction. > Harmless to human body: is harmless with heart pacemaker, pregnant women, magnetic floppy, recording tapes, etc. 
6.	<p>MODEL:XYT2101-II (6 ZONES)</p> <p>Technical parameter Electric current: AC85V~264V/50-60HZ Power: <20W, low consume, low radiation Net weight: 90KG Workplace environment: -20℃--+50℃ Standard: GB15210-2003, CE Standard External size: 2230mm(H)X835mm(W)X580mm(D) Standard Internal size: 1990mm(H)X700mm(W)X500mm(D)</p> <p>Characteristic & Function</p> <ul style="list-style-type: none"> > Program Self-diagnostic when power on, automatically checking left and right door panel, LED light and choose the best working frequency. > Six mutual over-lapping detecting zones, Simultaneous alarm from multi-zones; > Sensitivity adjustable: Each zone has 255 degree sensitivity level, three patterns: High, middle, Low for different requirements. Preset the metal size, weight, volume, location to exclude the coin, key, belt. > Sound Alarm: 1-25s alarm time, 255 different sound volume for choose > LED alarm: Six LED strip on the top control unit, indicate the alarm zones > Automatically count passengers and alarm times > Password protection, only the authorized person can operate. > Easy assembly: designed with only 2 pieces cables and 8 screws, Simply-to-follow instruction. > Harmless to human body: is harmless with heart pacemaker, pregnant women, magnetic floppy, recording tapes, etc. 