





DOBIY LAZERINIAI ATSTUMO MATAVIMO PRIETAISAI

Eil. Nr.	Vaizdas	Modelis	Matavimo riba (m)	Tikslumas (±mm)	Matmenys (mm)	Matavimo greitis (s)	Specifikacija
1.	 <p>T-Series</p>	T-40	40	2	121x56x28	1-1,2	Distance, Area, volume measurement Indirect measurement using Pythagoras Addition/subtraction Continuous measurement Minimum/maximum distance tracking Display illumination and multi-line display Dust protect/splash-proof: IP54 History measurement records: 10 Auto laser switch off: after 0.5min Auto instrument switch off: after 3min Battery life: up to 5,000 measurements
2.		T-70	70	2	121x56x28	1-1,2	
3.		T-100	100	2	121x56x28	1-1,2	
4.	 <p>D-Series</p>	D-40	40	2	113x46x25	1-1,2	
5.		D-60	60	2	113x46x25	1-1,2	
6.		D-80	80	2	113x46x25	1-1,2	
7.		D-100	100	2	113x46x25	1-1,2	
8.	 <p>D+ Series</p>	D+40	40	2	120x55x28	1-1,2	
9.		D+60	60	2	120x55x28	1-1,2	
10.		D+80	80	2	120x55x28	1-1,2	
11.		D+100	100	2	120x55x28	1-1,2	
12.	 <p>X-Series</p>	X-40	40	2	118x49x27	0,8-1	
13.		X-60	60	2	118x49x27	0,8-1	
14.		X-80	80	2	118x49x27	0,8-1	
15.		X-100	100	2	118x49x27	0,8-1	
16.	 <p>X+ Series</p>	X+40	40	2	128x49x28	0,8-1	
17.		X+60	60	2	128x49x28	0,8-1	
18.		X+80	80	2	128x49x28	0,8-1	
19.		X+100	100	2	128x49x28	0,8-1	
20.	 <p>X150</p>	X150	150	2	128x49x28	0,8-1	