

Hardware Specifications:

Weight:	2.2 lbs. (1 kg)
Size:	6 x 2.5 x 5 in. (15.2 x 6.4 x 12.7 cm)
Power Supply:	(2) AA batteries (20 hours of use)
Accuracy (Typical):	1 yd. (1 m)
Accuracy (Max):	2 yds. (2 m)
Overhead cable / Stake:	440 yds. (400 m)
Phone pole / Stockpile:	875 yds. (800 m)
Tree / Tower:	1315 yds. (1200 m)
Rock Face / Building:	2190 yds. (2000 m)
Max Distance:	2400 yds. (2200 m)
Range Resolution:	1 yd. (1 m)
Temperature:	- 22 to + 140 F (-30 to + 60 C)
Environment:	Waterproof to IP 67 and NEMA 6

** Hardware Specifications show typical target accuracy & range. Max distances are approximate.*

Key Features:

- Custom backlit LCD display
- Audible and visual indicators
- RS232 serial output for electronic data storage
- Selective range gating for positive target acquisition
- Cumulative distance capability
- Determines the distance between two in-line objects
- Range offset

Basic Package Includes:

- Impulse 2K laser
- 3 to 9 X zoom scope
- Hand strap
- Tripod / monopod mounting bracket
- Operator's manual
- (2) AA batteries
- Padded carrying case

Optional Accessories:

- Tripod or monopod